

The MS 230 Multistripper has been developed to satisfy the requirements of removing floor coverings from smaller projects and confined areas

This compact, easy-to-operate machine offers the user a solution for commercial and domestic applications. Forward motion is achieved by manual effort made easier by the adjustable handle to suit different body heights. All components are manufactured from the highest grade materials ensuring strength and reliability.



Specifications		
Type	MS 230 Electric 110V	MS 230 Electric 230V
Part Number	MS 230-1	MS 230-2
Power Output	2.0hp/1.5kW	2.0hp/1.5kW
Voltage	110V	230V
Cycles	50/60Hz	50/60Hz
Machine Dimensions		
Length	685mm (27")	685mm (27")
Width	380mm (15")	380mm (15")
Height	787mm (31")	787mm (31")
Weight	45kg (99lbs)	45kg (99lbs)
Work Width	230mm (9")	230mm (9")
Engine/Motor	1400rpm	1400rpm

Accessories	Part No.	Description
MS 230	C301	Std Blade

Features

- Fully adjustable chassis to adjust blade angle
- Large diameter wheels for excellent mobility and stability
- Simple clamp arrangement for quick and easy blade change
- Optimum weight distribution to ensure high work rate
- Handle height adjustable for operator control

Applications

The removal of sheet vinyl, linoleum, cork, bonded carpet woodblock, tiles, debonded membranes, sports surfaces failed latex, build-up of excess materials in production areas, mortar/Plaster droppings from concrete floors in new build

UK & Europe Electrical Requirements (Plug and cable sizes available for other countries, please enquire for details)

Machine	Voltage	Plug Size	Cable Size	Max Cable Length	Transformer	Generator
MS 230-1	110V	16A 3 Pin	2.5mm 3 Core	30m (98')	3 kVA	5 kVA
MS 230-2	230V	16A 3 Pin	2.5mm 3 Core	30m (98')	-	5 kVA