

Many years of experience in the design and operation of surface preparation equipment have been integrated with the latest computer design technology to produce the MS 330 Multistripper



Since the MS 330 launch, this heavy-duty, power-driven machine has proved to be a popular choice, setting new industry standards for all floor strippers of this type. By combining many unique features in one machine, the MS 330 offers the user a totally effortless high performance stripping machine for the removal of materials in the toughest possible conditions.

Specifications

Type	Electric			Petrol/Gasoline
	1 Phase		3 Phase	
Part Number	MS 330-1	MS 330-2	MS 330-3	MS 330-4
Power Output	3.0hp/2.2kW	3.0hp/2.2kW	3.0hp/2.2kW	5.5hp/4.1kW
Voltage	110V	230V	400/460V	-
Cycles	50/60Hz	50/60Hz	50/60Hz	-
Machine Dimensions				
Length	1100mm (43.3")	1100mm (43.3")	1100mm (43.3")	1100mm (43.3")
Width	480mm (18.9")	480mm (18.9")	480mm (18.9")	480mm (18.9")
Height	1000mm (39.4")	1000mm (39.4")	1000mm (39.4")	1000mm (39.4")
Weight	132kg (290lbs)	132kg (290lbs)	132kg (290lbs)	126kg (277lbs)
Working Width	330mm (13")	330mm (13")	330mm (13")	330mm (13")
Engine/Motor	2800rpm	2800rpm	2800rpm	2800rpm

Features

- All support wheels power driven to provide excellent forward traction
- Handle height adjustable for operator comfort
- Manually operated positive drive clutch for forward drive/freewheel
- Minimal operator fatigue
- Extremely powerful, robust construction
- Simple clamp arrangement for quick and easy blade change
- Available in choice of electric or petrol/gasoline
- Blade angle adjustable to suit application



Accessories	Part No.	Description
MS 330	7007	Std Blade

Applications

The removal of sheet vinyl, linoleum, cork, bonded carpet woodblock, tiles, debonded membranes, sports surfaces, failed latex, build-up of excess materials in production areas, mortar/plaster droppings from concrete floors in new build

UK & Europe Electrical Requirements (Plug and cable sizes available for other countries, please enquire for details)

Machine	Voltage	Plug Size	Cable Size	Max Cable Length	Transformer	Generator
MS 330-1	110V	32A 3 Pin	4mm 3 Core	30m (98')	5 kVA	8 kVA
MS 330-2	230V	16A 3 Pin	2.5mm 3 Core	30m (98')	-	8 kVA
MS 330-3	400V	16A 5 Pin	2.5mm 4 Core	75m (246')	-	8 kVA